

8A27-DEKA

SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	100Ah
Capacity at C/20	92Ah
Weight	63 lbs. (29 kg)
Plate Alloy	Lead Calcium
Posts	Forged Terminals & Bushings
Container/Cover	Polypropylene
Operating Temperature Range	-40°F (-40°C) - 140°F (60°C)
Charge Voltage @ 68°F (20°C)	
Cycle	2.40 - 2.43VPC
Float	2.25 - 2.30VPC
Vent	Self-sealing (2 PSI operation)
Terminal	B (T876)




Rated non-spillable by ICAO, IATA and DOT

Made in the U.S.A. by East Penn Manufacturing Co., Inc.

Distributed by:


Valve-Regulated, Absorbed Glass Mat Technology



DIMENSIONS

Length (mm)	12.75 (324 mm)
Width (mm)	6.75 (171 mm)
Height (mm)	9.25 (235 mm)

**AGM Cycle Life vs Depth of Discharge at +25°C (77°F)
Based on BCI 2-hour Capacity**



MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com

