

Keep Heavy-Duty Equipment Running at Top Performance

Demanding commercial equipment requires nothing less than the most powerful, reliable batteries. This complete line of the toughest commercial product is specially engineered for durability while meeting high power ratings for heavy-duty engines.



Key Features and Benefits of the Deka Commercial Line

- Genuine calcium lead alloy provides longer waterless operation and extended battery life.
- Anchor-locked elements with full-frame grids and tight-packed commercial plates resist the damaging effects of vibration, delivering more powerper-pound than other batteries.
- Most of our commercial batteries contain premium "deep pocket" envelope separators, which protect the plates on all four sides to dramatically reduce shorting and extend service life.
- Special computer-aided design and manufacturing means more durability for heavy-duty line-haul trucks, buses, farm tractors and off-road equipment.



- Most popular sizes feature tough polypropylene cases which resist breakage and extend service life. Many are also available with handles and special terminals for easy installation.
- Deka offers the most complete line of enveloped calcium maintenance-free commercial batteries in the industry.
 Our line includes such hard-to-find group sizes as 5D.
- More than 300 quality control checks ensure the highest quality.
- Low maintenance and batteries with a hybrid construction require periodic water maintenance. Always check that the electrolyte covers the top of the plates before charging.

Commercial Batteries

| | PART NO. | PERFORMANCE LEVEL | | | WEIGHT (LB.) | MAXIMUM OVERALL DIMENSIONS | | | | | | | | |
|---------------------------|---------------------------------------|-------------------|--------------|-----------|--------------|----------------------------|---------|---------|------|--------|-----|------------|---------------|--|
| GROUP NO. | | | | | | LENGTH | | WIDTH | | HEIGHT | | CORE VALUE | FOOTNOTES | |
| | | CCA | R.C. | REF. CA | (LD.) | in | mm | in | mm | in | mm | VALUE | | |
| 8-VOLT COMMERCIAL SERVICE | | | | | | | | | | | | | | |
| 1 | 801 | 520 | 102 | 640 | 32 | 8-7/8 | 225 | 6-3/4 | 171 | 8-7/8 | 225 | 1.0 | 12,25 | |
| | 6-VOLT HEAVY-DUTY COMMERCIAL SERVICE | | | | | | | | | | | | | |
| 1 | 901MF | 640 | 130 | 785 | 33 | 9 | 229 | 6-7/8 | 175 | 8-3/4 | 222 | 1.0 | 21,25 | |
| 2 | 902 | 675 | 185 | 830 | 37 | 10-3/8 | 264 | 6-7/8 | 175 | 8-3/4 | 222 | 1.0 | 12,25 | |
| 3EH | 93EH | 875 | 250 | 1075 | 47 | 19-1/4 | 489 | 4-1/4 | 108 | 10 | 254 | 1.0 | 12,25 | |
| 4 | 904MF | 975 | 250 | 1200 | 48 | 12-1/2 | 318 | 6-7/8 | 175 | 9-1/2 | 241 | 1.5 | 21,25 | |
| 5D | 905D | 880 | 250 | 1080 | 54.5 | 13-3/8 | 340 | 7-1/8 | 181 | 9-1/4 | 235 | 1.5 | 12,25 | |
| | 12-VOLT HEAVY-DUTY COMMERCIAL SERVICE | | | | | | | | | | | | | |
| 3ET | 3ET | 3ET | 3ET | 3ET | 3ET | 3ET | 489 | 4-1/4 | 108 | 9-7/8 | 251 | 1.0 | 12,25 | |
| 4D | 904D | 1050 | 290 | 1290 | 97 | 20-1/2 | 520 | 8-5/8 | 219 | 9-7/8 | 251 | 3.0 | 12,17,21,22 | |
| 4DLT | 94DLT | 850 | 240 | 1045 | 78.5 | 20 | 508 | 8-1/8 | 206 | 8-1/8 | 206 | 2.0 | 12,19,25 | |
| 8D - | 908DFT | 1425 | 440 | 1755 | 127 | 20-3/4 | 527 | 11 | 279 | 10 | 254 | 4.0 | 12,17,21,22 | |
| 9D | 708D | 1100 | 325 | 1355 | 114.5 | | | | | | | 4.0 | 12,17,25 | |
| 17TF | 917TF | 530 | 140 | 650 | 63 | 17 | 432 | 6-7/8 | 175 | 8 | 203 | 1.5 | 11,15,19,25 | |
| 28 | 928MF | 550 | 100 | 675 | 42.5 | 10-1/4 | 260 | 6-3/4 | 171 | 9-1/2 | 241 | 1.0 | 21,22,X | |
| 30H | 930H | 650 | 150 | 800 | 51 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 19,21,22 | |
| | 1231MF | 1000 | 185 | 1230 | 60 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 17,19,21,22,X | |
| 31 | 1131MF | 950 | 175 | 1170 | 56.5 | | | | | | | 1.5 | 17,19,21,22,X | |
| 31 | 1031MF | 760 | 170 | 935 | 53.5 | | | | | | | 1.5 | 17,19,21,22,X | |
| | 931MF | 650 | 150 | 800 | 52 | | | | | | | 1.5 | 17,19,21,22,X | |
| | 1231PMF | 1000 | 185 | 1230 | 60 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 17,19,21,22 | |
| 31P | 1131PMF | 950 | 175 | 1170 | 56.5 | | | | | | | 1.5 | 17,19,21,22 | |
| 317 | 1031PMF | 760 | 170 | 935 | 53.5 | | | | | | | 1.5 | 17,19,21,22 | |
| Γ | 931PMF | 650 | 150 | 800 | 52 | | | | | | | 1.5 | 17,19,21,22 | |
| | | 1 <u>2-V</u> | OLT HEAVY-DI | JTY COMME | RCIAL SEVE | RE SER | /ICE/DL | JAL PUF | POSE | | | | | |
| 31 | 7T31 | 730 | 190 | 900 | 62 | | | | | | | 1.5 | 17,19,21,22,X | |
| 31P | 7T31P | 730 | 190 | 900 | 62 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 17,19,21,22 | |
| 31 | DP31CS | 700 | 185 | 860 | 57 | | | | | | | 1.5 | 17,19,21,22,X | |

- Batteries are maintenance-free calcium grids, except where noted
- Batteries manufactured in polypropylene cases & covers, except where noted
- Batteries manufactured in black cases & covers
- Terminal s are SAE Posts, unless noted
- Weights are approximates
- CA @ 32°F are approximations and for comparison only
- CCA and RC ratings conform to B.C.I. specifications

FOOTNOTES:

- 11 Low maintenance low antimony grids
- 12 Hybrid construction
- 15 Hard rubber, one-piece cover construction
- 17 Includes handle
- 19 Includes lifting ledges
- 21 Anchor lock elements
- 22 Flush manifold vented cover
- 25 With individual vent caps
- X 3/8" 16 stainless steel stud posts

TERMINAL:



PROPOSITION 65 WARNING: Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. WASH HANDS AFTER HANDLING.

MEMBER:



